INDEXED <u>Kam</u> FOLLOW UP. PROOFED SCANNED

Instrument #: 2014-1981 89/28/2014 11:07:47 AM Total Pages: 1 PLC PLAT CORNER CER Recording Fee: \$7.00 Transfer Tax: \$0 Denise Meeves, Recorder, Crawford County Iowa

WILKE LAND SURVEYING INC. 401 1800th Street

Panama, lowa 51562

(712)489-2898

UNITED STATES PUBLIC LAND SURVEY CORNER CERTIFICATE


SECTION 35 TOWNSHIP 82N RANGE 41W COUNTY CRAWFORD Reason for Certificate: (No record Certificate)

Monument Description and Remarks:

N1/4 CORNER - Set 5/8" diameter by 24" long rebor with N1/4 CURNER — Set 3/8 diameter by 24 long repor with orange cap PLS #17048 (0.5' deep) on the Northerly slope of a drainage ditch using WPA ties and a fence to the South. The WPA ties were referenced to the Southeasterly edge of U.S. Highway 30 in 1942. The existing centerline of U.S. Highway 30 was offset a 1942 lane width of 9' to establish the previous Southeasterly edge of the povement.

SW CORNER NW1/4 NE1/4 - Set 5/8" diameter by 24" long rebar with arange cap PLS #17048 (0.5' deep) at the midpoint of the West line of the NE1/4. Corner is 2.3' Southeasterly of the centerline of Duntop Street.

CENTER - Set 5/8" diameter by 24" long rebar with arange cap PLS #17048 (0.4' deep) on the Northwest side of fence corner post with fences South and East.



N1/4 CORNER SEC. 35, T82N, R41W (Set 5/8" dia. rebar w/orange cap PLS #17048, 0.5' deep on the Northerly slope of drainage ditch) 56.68° perp. to € of Hwy. 30.

€ of drainage ditch 9.37" North to "X" nails in South face of power pole. 89.55' SW to "X" nails in North face of fence corner post.

Pole Building 34.95' NE to SE corner of steel pole building. 47.24' NW to SW corner of steel pole building. -6.74" East to "X" nails in North face CENTER SEC. 35, TB2N, R41W (Set 5/8" dia. rebar of brace post. w/orange cap PLS \$17048, 0.4' deep)

SW CORNER NW1/4 NE1/4 SEC. 35, T82N, R41W (Set 5/8" dia. rebar w/orange cap PLS #17048, 0.5' deep)

17.84' NW to cut "X" in-top of conc. headwall © NW corner of culvert.

44.42' SW to "X"-1 noils in East face of NE1/4 and the & of Dunlap Street. new fence cor. post.

O LAND SUP DEAN A WILKE 17048 5.56' North to iron pin w/orange cop PLS #17048 at the intersection of the West line of the AWO! Mannan N

ALL DISTANCES ARE HORIZONTAL

hereby certify that this land surveying document was prepared or the related survey work was performed by me or under my direct sersonal supervision and that I am a duly licensed Land Surveyor

Section Twp. Range 82N 41W 35

N1/4 CORNER SW CORNER NW1/4 NE1/4 41W 35 82N CENTER 35 82N 41W

List Corners to be Indexed

Corner

21.80' NE to cut "X" in

top of conc. headwall

SE corner of culvert.

My Scenee renewal date is December 31, 2015

Pages or sheets covered by this seal: This page only