

2/1

Using Co. BK # 8 P.P. # 153 as

reference we dug for witnesses

corners. Found 1/2" x 1/2" iron rod

on east side of road. Set C.M.

35' west of this witness

corner in line with F&W

fence. Set C.M. 18" below road surface

from 25' E of power pole

38.3 E of corner post

28.5 NE of x on W head of Can. Ck.

38.8 SW of 6" boarder

34.7 NW of tel pole

35

Dug hole 4' x 12' x 15' deep. Found 2" x 10"

walnut stake at a depth of 14" brick

bats at a depth of 18" 4" x 16" black

walnut stake at a depth of 3 1/2'

lowered and set C.M.

7/25

40.8 S from cor post

17.6 N " " fe line

14.9 W.N.W " " tele pole

FOUND FEB. 11, 1958

1/2" IRON ROD TO SURF

LOCHMILLER

Found & Set 6-12-42

Joans-Kessel-Limbracht

Chief - Champion

11/19/59

75.0'

power pole

45.4

34.1

34.8

36.3

tel pole

cor. P

cor. 1' south of F

fence from west

Set lead plug on 2.504 cut 6/16/64

REAR-45 SUC

KTUNE CLARY

Found 5.3.39

40.8

cut post

14.9

TEL. POLE

17.6

FE-LINE

FE-LINE

FE-LINE