

Crawford County Recorder Denise Meeves Fee Book 2008-3089 11/12/2008 @08:48AM PLC PLAT CORNER CER Book: Page: \$7.00


Pages: 1



PREPARED BY & RETURN TO MIKE SCHULTE, SNYDER & ASSOCIATES, INC. 2727 SW SNYDER ROAD, ANKENY, IOWA 50023 (888) 964-2020 UNITED STATES PUBLIC LAND SURVEY CORNER CERTIFICATE OF Land Survey Monuments situated in Section 14 Township 83 N 37 W , of the Fifth Principal Meridian, CRAWFORD , Courty Recorder RAWFORD , County, Iowa. _ in County Recorder's Office. Previously recorded in (SEC BCLUM) (book, page, document number, ect.) (Show reason for preparing this certificate, the evidence and detailed procedures used in establishing the corner positions and monumentation found or placed.) Monument Description and Remarks: WEST 1/4 CORNER SEC 14-83-37 USED ENGINEERS THE TO FIND REMANDER OF CONCRETE MONUMENT, ONLY 4" WERE LEFT OF MONUMENT, POSITION WAS COMPROMISED. EXCAVATED FURTHER TO FIND LIMESTONE AS DESCRIBED IN COUNTY NOTES. LOWERED THE REBAR SET FOR LOCATING PURPOSES & DISCARDED CONCRETE MONUMENT AT EAST CORNER POST. TOP OF STONE 10" DEEP, ALL TIES TO CENTER OF STONE. CENTER OF SECTION 14-83-37 NO RECORD OF TIES FOUND. USED N, S, E & W1/4 CORNERS TO VERIFY CENTER OF SECTION POSITION SET 1/2" REBAR WITH YELLOW CAP #17979 0.3' ABOVE SURFACE (Show a minimum of three reference ties to durable physical objects, relevant monuments and physical conditions that will enable recovery of the corner.)

NAD83 (1996) Lat: 42°80'06.19636"N Long: 95°07'50.34362''W


WEST 1/4 CORNER



NAD83 (1996) Lat: 42°00'05.80262"N Long: 95°07'15.80063"W



CENTER OF SECTION SET 1/2" REBAR 0.3' ABOVE GROUND



NOTE: ALL DISTANCES MEASURED HORIZONTAL



License Humber 17979

o Maneual Bate is Do ts covered by this sect: SHEET LOF 1

List Corners to be Indexed

Corners	Section	Twp	Range
W CORNER	14	83	37
e corner	15	83	37
CENTER OF SECTION	14	83	37

TECH: MLS/SLG PN: 83-37-14-W & CTR 108.0781 DATE: 10/28/08