MG_ DEXECUT FOLLOW UP DM PROOFED.

02 DEC -6 PM 1: 25

INST. NO. 2002 - 3977
DENISE MEEVES. RECORDER
Denise William
FFE TOP Many rites

PREPARED BY: J. SCOTT SHEVEL L.S., KUEHL AND PAYER LTD., 423 WEST MAIN ST., SAC CITY, IA 50583 PH. (712)662-7859 UNITED STATES PUBLIC LAND SURVEY CORNER CERTIFICATE OF _TOWNSHIP 83 NORTH. LAND SURVEY MONUMENTS SITUATED IN SECTION 18 WEST, OF THE 5TH PRINCIPAL MERIDIAN, _ CRAWFORD COUNTY, IOWA. 37 PREVIOUSLY RECORDED IN BOOK_ PAGE MONUMENT DESCRIPTION AND REMARKS: 1.) W 1/4 CORNER 18-83-37: ACCORDING TO COUNTY RECORDS, NO MONUMENT WAS FOUND IN PREVIOUS SEARCH; SET 5/8" REBAR WITH RED PLASTIC CAP STAMPED "S. SHEVEL 11810", 6" DEEP, EQUIDISTANT ON A LINE BETWEEN THE SW & NW CORNERS 2.) SW CORNER 18-83-37: FOUND 1" BAR 18" DEEP 3.) S 1/4 CORNER 18-83-37: FOUND BROKEN OFF CONCRETE MONUMENT 8" DEEP; SET 1/2" REBAR ON SOUTH SIDE TO AID IN LOCATION **PLAN - VIEW** 1.) W 1/4 CORNER 18-83-37 SET 5/8" REBAR WITH RED PLASTIC CAP STAMPED "S. -83-N SHEVEL 11810", 6" DEEP WOOD POST R-37-W CRAWFORD COUNTY 64.25 S.M. IN S.M. IN CORNER POST S.M. IN BRACE S.M. IN k3.89 GATE POST CORNER POST POST [5] GATE POST 3.) S 1/4 CORNER 8 18-83-37 FD. BROKEN OFF **CONCRETE MONUMENT 8"** DEEP; SET 1/2" REBAR ON SOUTH SIDE TO AID IN 2.) SW CORNER LOCATION 18-83-37 " BAR 18" DEEP S.M. IN TOP OF CORNER S.M. IN TOP OF WOOD POST 5/8" REBAR WITH ALUM. S.M. IN S.M. IN CAP STAMPED "SECTION CORNER REF. PT." CORNER S.M. IN TOP OF WOOD POST POST %/ %/ POST POST S.M. IN TOP OF WOOD POST 1.65 15. AST. S.M. = SURVEY MARKER PLASTIC REFERENCE DISK AS SHOWN BELOW b STOP SIGN POST



I hereby certify that this land surveying document was prepared and the related survey work was performed by me or under my direct personal supervision and that I am a duly licensed Land Surveyor under the laws of the State of Iowa

Dest Mure 12/2/02 J. Scott Shevel Date:

License Number 11810 My license renewal date is December 31, 2003 Pages covered by this seal 1

List Corners to be Indexed			
Corners	Section	Township	Range
1) W 1/4	18	83	37
2) SW	18	83	37
3) S 1/4	18	83	37
			PN: 020628 DRAWN: JMK