INDEXED A PROOFED SCANNED

Instrument #: 2014-1878
09/15/2014 11:47:20 AM Total Pages: 1
PLC PLAT CORNER CER
Recoording Fee: \$7.00 Transfer Tax: \$0
Denise Neeves, Recorder, Crawford County Iowa

8}}} ||\$\frac{\frac{1}{2}}{2} ||\$\frac{1}{2} ||\$\fr

WILKE LAND SURVEYING INC.

401 1800th Street

Panama, lowa 51562

(712)489-2898

UNITED STATES PUBLIC LAND SURVEY CORNER CERTIFICATE


SECTION 5 TOWNSHIP 82N RANGE 37W COUNTY CRAWFORD Reason for Certificate: (No record Certificate)


Monument Description and Remarks:

W1/4 CORNER - Found 1/2" diameter iron pin (1.0' deep). Corner is in line with fence to the East.

S1/4 CORNER - Found iron pin with yellow cap PLS #6806 (0.2" deep). Corner is in line with fence to the South, and approximately 10' West of fence to the North.

CENTER - Set 5/8" diameter by 24" long rebor with orange cap PLS #17048 (flush) between double fence corner posts with fences North, East, South, and West. Corner is 0.58' Southeast of "X" noils in Southeast face of fence corner post, and 0.64' Northwest of "X" noils in Northwest face of fence corner post.





CENTER SEC. 5, T82N, R37W (Set 5/8" dia. rebar w/orange cap PLS #17048)

ALL DISTANCES ARE HORIZONTAL

S1/4 CORNER SEC. 5, T82N, R37W (Fnd. iron pin w/yellow cap PLS #5806)

E "T" AVENUE-

49.33' SW to "X" nails in NE face of power pole.

33.22' South to "X" nails in North face of fence corner post.

+/- 10' West of fence North

> LAND SU DEAN A WILKE **17048** AWO!

34	U.	, ,	w	ιo	- A	
noi	ı	in	No	rth	fo	ce
		oce				
O1	v	ur.c		OSI	•	

List Corr	ners to be	Indexed	
Corner	Section	Twp.	Range
W1/4 CORNER	5	82N	37W
S1/4 CORNER	5	82N	37W
CENTER	5	82N	37W

hereby certify that this land surveying document was prepared or the related survey work was performed by me or under my direct bersamel supervision and that I am a duly licensed Land Surveyor under the logs of the State of lows.

Door A. Wilke

My license renewal date is December 31, 2015

Poges or sheets covered by this seal: This page only