INDEXED L PROOFED SCANNED

Instrument #: 2014-1878
09/15/2014 11:47:20 AM Total Pages: 1
PLC PLAT CORNER CER
Recording Fee: \$7.00 Transfer Tax: \$0
Denise Neeves, Recorder, Crauford County Iowa

## 

WILKE LAND SURVEYING INC.

401 1600th Street

Panama, lowa 51562

(712)489-2898

## UNITED STATES PUBLIC LAND SURVEY CORNER CERTIFICATE

SECTION 5 TOWNSHIP 82N RANGE 37W COUNTY CRAWFORD


Reason for Certificate: (No record Certificate)


## Manument Description and Remarks:

W1/4 CORNER - Found 1/2" diameter iron pin (1.0' deep). Corner is in line with fence to the East.

S1/4 CORNER - Found iron pin with yellow cap PLS #6806 (0.2' deep). Corner is in line with fence to the South, and approximately 10' West of fence to the North.

CENTER - Set 5/8" diameter by 24" long rebar with orange cap PLS #17048 (flush) between double fence corner posts with fences North, East, South, and West. Corner is 0.58' Southeast of "X" nails in Southeast face of fence corner post, and 0.64' Northwest of "X" nails in Northwest face of fence corner post.





CENTER SEC. 5, T82N, R37W (Set 5/8" dia. rebor w/orange cap PLS #17048)

SALL DISTANCES ARE HORIZONTALS

S1/4 CORNER SEC. 5, T82N, R37W (Fnd. iron pin w/yellow cap PLS #6806)

E T AVENUE-

34.03' SW to "X"---

of brace post.

49.33' SW to "X" nails in NE face of power pole.

33.22' South to "X" noils in North face of fence corner post.

+/- 10' West of fence North



	Corners to be Section	Indexed Twp.	Ronge
Corner W1/4 CORNER S1/4 CORNER CENTER	5	82N	37W
S1/4 CORNER	5	82N	37W
CENTER	5	82N	37W

by cartify that this land surveying document was prepared or folded survey work was performed by me or under my direct fol supervision and that I om a duly licensed Land Surveyor the logs of the State of lows.

Deon A. Wilke

License number 17048

My license renewal date is December 31, 2015

Pages or sheets covered by this seal: This page only